

ENDURA® STYLE UPDOWN

LED WALL LUMINAIRES IN CLASSIC DESIGN





1
ENDURA STYLE UpDown
12 W AL



2
ENDURA STYLE UpDown
12 W DG



3
ENDURA STYLE UpDown
12 W WT



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t[h] ²	W	lm	lm/W ³	K	CRI	°
ENDURA STYLE UpDown 12 W AL	4058075205604	1	Aluminum	Aluminum	30000	11.50	700	A++/A+/A	3000	≥80	110
ENDURA STYLE UpDown 12 W DG	4058075214057	2	Dark gray	Aluminum	30000	11.50	700	A++/A+/A	3000	>80	110
ENDURA STYLE UpDown 12 W WT	4058075214071	3	White	Aluminum	30000	11.50	700	A++/A+/A	3000	>80	110

Product name	IP	lm	l [mm]	w [mm]	h [mm]	kg
ENDURA STYLE UpDown 12 W AL	IP44	15000	55.0	90.0	160.0	6
ENDURA STYLE UpDown 12 W DG	IP44	15000	55.0	90.0	160.0	6
ENDURA STYLE UpDown 12 W WT	IP44	15000	55.0	90.0	160.0	6

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEL) on a scale of A++ (highest efficiency) to E (lowest efficiency).