

## LED BULKHEAD

VERSATILE, EASY TO INSTALL FUNCTIONAL LUMINAIRES





1  
LED BULKHEAD  
11 W 4000 K WT



2  
LED BULKHEAD  
11 W 4000 K BK



3  
LED BULKHEAD  
6 W 4000 K WT



4  
LED BULKHEAD  
6 W 4000 K BK



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t[h] <sup>2</sup>	W	lm	Energy efficiency grade <sup>3</sup>	Temperature range
LED BULKHEAD 11 W 4000 K WT	4058075271661	1	White	Polycarbonate (PC)	20000	11.00	800	A++/A+/A	-20...+40
LED BULKHEAD 11 W 4000 K BK	4058075271685	2	Black	Polycarbonate (PC)	20000	11.00	800	A++/A+/A	-20...+40
LED BULKHEAD 6 W 4000 K WT	4058075271586	3	White	Polycarbonate (PC)	20000	5.50	450	A++/A+/A	-20...+40
LED BULKHEAD 6 W 4000 K BK	4058075271647	4	Black	Polycarbonate (PC)	20000	5.50	450	A++/A+/A	-20...+40

Product name	K	CRI	Beam angle	IP	Beam diameter [mm]	Beam length [mm]	Beam width [mm]	Beam height [mm]	Beam area [mm²]
LED BULKHEAD 11 W 4000 K WT	4000	≥80	120	IP54	100000	216.0	143.0	79.0	6
LED BULKHEAD 11 W 4000 K BK	4000	≥80	120	IP54	100000	216.0	143.0	79.0	6
LED BULKHEAD 6 W 4000 K WT	4000	≥80	120	IP54	100000	168.0	117.0	70.0	8
LED BULKHEAD 6 W 4000 K BK	4000	≥80	120	IP54	100000	168.0	117.0	70.0	8

<sup>1</sup> The exact terms and conditions can be found at [www.ledvance.com/consumer/services/guarantee](http://www.ledvance.com/consumer/services/guarantee) | <sup>2</sup> Average lifetime in hours | <sup>3</sup> Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEI) on a scale of A++ (highest efficiency) to E (lowest efficiency).