

PRODUCT DATASHEET

SMART+ CLOUD CAMERA

Smart+ Camera Cloud | Outdoor Smart Camera Cloud



Areas of application

- Outdoor use (IP44)
- Garages
- Entrance areas

Product benefits

- Easy and quick installation
- Increased perception of safety thanks to high brightness
- The recorded data is saved on the unit's memory card or cloud storage
- High-quality materials

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 6.0 or iOS 11.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Built in speaker and alarm siren
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFi
- Type of protection: IP44
- HD Live view camera
- 3 MP camera
- Talk from mobile phone to camera



- Automatic night mode
- Motion sensor with activity schedule
- Auto record of motions (SD card required)

TECHNICAL DATA

Electrical data

Nominal wattage	15.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	110.000 mA
Power factor λ	> 0.5
Protection class	II

Photometrical data

Luminous flux	1000 lm
Total luminous flux of contained light sources	1400 lm
Luminous efficacy	66 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥ 80
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Beam angle	110 °

Dimensions & Weight

Length	100.00 mm
Width	80.00 mm
Height	252.00 mm
Product weight	500.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP44
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Number of switching cycles	12500
----------------------------	-------

Sensor

Type of sensor	Motion / Daylight
Sensor controlled switching time	60 s
Detection range of motion sensor	3...7 m
Detection threshold of daylight sensor	0...20 lx

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No


Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
----------------	--

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Mounting screws and dowels included
- SD card not supplied
- Compatible with SD card type (SD/SDHC/SDXC)
- SD Class recommended 120-160MB/s
- Minimum card capacity 8GB/Maximum 128GB

DOWNLOAD DATA

DOWNLOAD DATA	
	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075763401	Folding box 1	120 mm x 265 mm x 100 mm	580.00 g	3.18 dm ³
4058075763418	Shipping box 2	285 mm x 140 mm x 200 mm	1375.00 g	7.98 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.