Kanlux

19442   MORTA CT-DSO50-SR

Ceiling-mounted spotlight fitting

5905339194428

A wide range of the Kanlux MORTA holder models will allow making very original arrangements in each house. Kanlux MORTA meet expectations of everyone that highly values products of high quality, characterized by attractive and original design.

GENERAL DATA:

Colour: silver
Necessity of using self-shielding lamps: yes
Place of assembly: Recessed mount in the ceiling
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
The product is not suitable to be installed on a normally flammable surface: >35W
The product is not suitable to be covered with a heat-insulating material: yes
Height [mm]: 28
Diameter [mm]: 90
Assembly hole [mm]: Ø65-70

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC
Maximum power [W]: max 10
Class of protection against electric shock: III
Light source: MR16
Light source included: no
Cap: Gx5,3
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: glass
Connection type: Free cable ends
Wire length [m]: 0.12
Wire diameter [mm²]: 0.75
Lighting-fixture angle regulation: none
IP class: 20

LOGISTIC DATA:

Packaging method: 50
Number of units in the secondary packaging: 1
Number of units in the packaging: 50
**Net unit weight [g]**: 134
Grammage [g]: 167.6
Length of a unit pack [cm]: 10.5
Width of a unit pack [cm]: 3
Height of a unit pack [cm]: 10.5

EN

19442 MORTA CT-DSO50-SR

Ceiling-mounted spotlight fitting

Ø65-70

28

10

Ø90

Weight of a cardboard box [kg]: 8.38
Width of a cardboard box [cm]: 18
Height of a cardboard box [cm]: 23
Length of a cardboard box [cm] : 54
Volume of a cardboard box [m³]: 0.022356

Date of issue: 15.11.2022, 06:11
We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.