

PRODUCT DATASHEET SENSOR WALL 110DEG IP44 WT

SENSOR WALL 110DEG | Stand-alone motion and light sensors for wall mounting with 110° detection range



Areas of application

- Outdoor
- Corridors, entrance areas
- Garages
- Basement
- Arcade passage

Product benefits

- Sensor for optimized energy savings

Product features

- Switch-on by movement
- Type of protection: IP44
- Protection class: II




TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	П

Dimensions & Weight

Length	60.00 mm
Width	77.00 mm
Height	72.00 mm
Product weight	89.00 g



Materials & Colors

Product color	White	
Body material	Polycarbonate (PC)	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-10+40 °C	
Temperature range at storage	-25+70 °C	
Type of connection	Screw terminal, 3-Pole	
Type of protection	IP44	
Dimmable	No	
Mounting type	Surface	
Mounting location	Wall	

Lifespan

Lifespan L70/B50 at 25 °C	50000 h

Sensor

Type of sensor	Light / Motion	
Sensor technology	Passive infrared (PIR)	
Sensor detection angle	110 °	
Sensor controlled switching time	2 s15 min	
Detection range of motion sensor	12 m	
Detection threshold of daylight sensor	11000 lx	

Certificates & Standards

Standards CE / EAC / UKCA

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction
PDF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075244733	Folding box 1	67 mm x 80 mm x 94 mm	112.00 g	0.50 dm ³
4058075244740	Shipping box 8	170 mm x 144 mm x 204 mm	1273.00 g	4.99 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

May 26, 2023, 12:06:20 SENSOR WALL 110DEG IP44 WT