


# PRODUCT DATASHEET

## SMART+ Wifi Orbis Claria 490mm RGB + TW

Smart+ Orbis Ceiling | Smart decorative ceiling with main and side light TW RGB and dimmable



---

### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

---

### Product benefits

- Easy and quick installation
- Tunable White and RGB
- Main light and side light

---

### Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Network protocol: WiFi
- Adjustable color temperature via Tunable White: 2,700...6,500 K



## TECHNICAL DATA

### Electrical data


Nominal wattage	32.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	180.000 mA
Inrush current time $T_{h50}$	350 $\mu$ s
Max. no. of lum. on circuit break. B16 A	5
Max. no. of lum. on circuit break. C16 A	8
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	I

### Photometrical data

Luminous flux	3150 lm
Total luminous flux of contained light sources	4200 lm
Luminous efficacy	98 lm/W
Color temperature	2700...6500 K
Light color (designation)	Tunable White / RGB
Color rendering index Ra	> 80
Standard deviation of color matching	$\leq 6$ sdc <sub>m</sub>
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0
Beam angle	360 °

### Dimensions & Weight

Diameter	490.00 mm
Height	95.00 mm
Product weight	3300.00 g



### Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C

### Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	25000

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

### Additional product data

## Product remark

Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.

## EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

## DOWNLOAD DATA

## Documents and certificates



User instruction



Installation guide



Declarations Of Conformity CE



Declarations Of Conformity UKCA

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075754775	Folding box 1	137 mm x 537 mm x 538 mm	3682.00 g	39.58 dm <sup>3</sup>
4058075754782	Shipping box 3	555 mm x 435 mm x 560 mm	12587.00 g	135.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.