

OLLO[®] EXCLUSIVE

Sensor ready system

Advantages
 High brightness and energy efficiency
 Sensor ready system
 Waterproof and dustproof
 Easy installation and use
 Safety and eco-friendliness
 Instant activation without delays

4000K NEUTRAL WHITE

150W

15000Lm

IP65
Waterproof

110°

VS121C-150W-40K
 Power: 150W
 Voltage: AC220-240V, 50-60Hz
 Luminous flux: 15000Lm
 Protection class: IP65
 Size: 337x262x31.5 mm
 Color temperature: 4000K
 LED Type: SMD2835
 CRI: > 80
 PF: > 0.9
 Material: Aluminum, PC, glass
 Warranty: 3 years

4 752233 014830

ENERGY

VISIONAL GLOBAL TRADING LIMITED
LED FLOODLIGHT VS121C-150W-40K

A

B

C

D

E

F

G

F

150

kWh/1000h

2019/2015



TEHNISKIE DATI
TECHNICAL DATA**Elektriskie dati**
Electrical data

Jauda / Wattage	150W
Spriegums / Voltage	AC220-240V
Tikla frekvence / Mains frequency	50/60 Hz
Jaudas koeficients / Power factor	PF > 0.9

Fotometriskie dati
Photometrical data

Gaismas plūsma / Luminous flux	15000 Lumen
Gaismas temperatūra / Color temperature	4000K
Gaismas krāsa / Light color	Neitrāli balts / Neutral white
Krāsu atveidošanas indekss / Color rendering index	CRI > 80
Stara leņķis / Beam angle	110°

Izmēri
Dimensions

Garums / Length	337 mm
Platums / Width	31.5 mm
Augstums / Height	262 mm

Pielietojums un sertifikāti
Application and certificates

Materiāls / Material	Alumīnijs, PC, stikls / Aluminum, PC, glass
Darba temperatūra / Operating temperature	-40C ... +55C
Resurss / Resource	25 000h
Aizsardzības klase IP / Protection class IP	IP65
Energoefektivitātes klase / Energy efficiency class	F
Sertifikāti / Certificates	CE, EMC, RoHS, IES
Garantija / Warranty	3 gadi / 3 years