



Ledinaire panel

RC065B LED34S/840 PSU W60L60 NOC

Ledinaire panel, 34 W, 600x600 mm, 3400 lumen, 4000 K

The Philips Ledinaire panel Gen4 (RC065B) range features a selection of popular off-the-shelf LED luminaires that come with Philips high quality levels at a competitive price. Reliable, energy efficient and affordable, this latest generation of 600 x 600 mm Ledinaire LED panel lights are designed for diffuse, comfortable lighting in a wide range of general lighting applications. Our range of Ledinaire panel lighting is also available with accessories for easy installation on different types of ceilings – just what you need

Product data

General Information		Operating and Electrical	
Lighting Technology	LED	Luminaire light beam spread	120°
Driver included	Yes	Unified glare rating CEN	22
Number of gear units	1 unit	Operating and Electrical	
Service tag	No	Input Voltage	220-240 V
Value ladder	Value	Line Frequency	50 or 60 Hz
Light source replaceable	No	Input Frequency	50 or 60 Hz
Light Technical		Inrush current	16 A
Luminous Flux	3,400 lumen	Inrush time	0.18 ms
Saturated Red (R9)	<50	Power Consumption	34 W
Correlated Color Temperature (Nom)	4000 K	Power Factor (Fraction)	0.9
Luminous Efficacy (rated) (Nom)	100 lm/W	Connection	Push-in connector 2-pole
Color rendering index (CRI)	≥80	Cable	-
Flickering value (PstLM)	1	Number of products on MCB of 16 A type B	32
Stroboscopic effect value (SVM)	0.4	Temperature	
Light source color	840 neutral white	Ambient temperature range	-10 to +25 °C
Optic type	Beam angle 120°		

Ledinaire panel

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover/lens material	Acrylate
Fixation material	-
Housing Color	White
Optical cover/lens finish	Opal
Overall length	595 mm
Overall width	595 mm
Overall height	34 mm
Dimensions (Height x Width x Depth)	34 x 595 x 595 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Warranty period	3 years
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM≤5
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	7.5 %
50000 h	
Lumen maintenance at median useful life*	L80
50000 h	
Lumen maintenance at median useful life*	L70
75000 h	

Application Conditions


Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes

Product Data

Full product code	871869979180399
Order product name	RC065B LED34S/840 PSU W60L60 NOC
Order code	911401885080
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material number (12NC)	911401885080
Full product name	RC065B LED34S/840 PSU W60L60 NOC
EAN/UPC - Case	8718699791810



Dimensional drawing



Ledinaire panel

