# **OSRAM**

# **ULTRA LIFE H4**

Longer life and 4 year guarantee





#### 4 year OSRAM guarantee

For a worry-free driving pleasure. Refer to www.osram.com/am-guarantee for precise conditions



#### Extra lifetime

Up to four times longer lifetime compared to standard halogen lamps



#### More durability

For longer replacement cycles and additional reliability and comfort



#### The durable light with up to four times longer lifetime

OSRAM ULTRA LIFE automotive lamps are a favorite when it comes to durability. They have an impressive lifespan up to four times longer compared to standard halogen lamps and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). OSRAM provides a 4 year guarantee for the reliable ULTRA LIFE headlight lamps (www.osram.com/am-guarantee). In addition to this, ULTRA LIFE headlight lamps have a modern design with silver cap (H4/H7/H11). They are therefore ideal for frequent drivers or people who use daytime running lights, and can also be used in clear-qlass headlights.

# Product datasheet

#### Technical data

# **Product information**

Application (Category and Product specific)	Halogen headlight lamp
---	------------------------

#### **General Product Information**

Global order reference	64193ULT
------------------------	----------

#### **Electrical Data**

Power input	75 / 68 W <sup>1)</sup>
Nominal voltage	12.0 V
Test voltage	13.2 V

<sup>1)</sup> Maximum

# **Photometric Data**

Nominal luminous flux	1650/1000 lm
Luminous flux tolerance	±15 / ±15 %

# **Physical Attributes & Dimensions**

Diameter	17.0 mm
Product weight	25.90 g
Length	82.0 mm
Lamp base	P43t

#### **Lifetime Data**

Lifespan B3	300 / 2000 hr <sup>1)</sup>
Lifespan Tc	700 / 3000 hr <sup>1)</sup>
Guarantee	3+1 years

<sup>1)</sup> Filament 1 / Filament 2

# Capabilities

Technology	HAL
------------	-----

#### **Certificates & standards**

# **Environmental & Regulatory Information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of declaration	09-07-2024

# Product datasheet

Primary article identifier	4008321416186   4008321416230   4062172395748   4062172387491   4008321421272   4052899031562   4062172250238   4008321416124
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	In work



ref\_pim\_amsp\_productinfographic

# Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321416131	ULTRA LIFE H4		- x - x -	5.62 dm <sup>3</sup>	
4008321416254	ULTRA LIFE H4		- x - x -	19.40 dm³	
4062172058674	ULTRA LIFE H4		- x - x -	4.22 dm <sup>3</sup>	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Download Data

	File
<b>大</b>	Brochures ULTRA LIFE Leaflet EN
D	Product movie ULTRA LIFE Trailer EN
	ref_pim_amsp_product360degreeimages ULTRA LIFE H4 64193ULT

#### References / Links

# Product datasheet

Guarantee terms are available at www.osram.com/am-guarantee

# **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

















