OSRAM

XENARC ULTRA LIFE D2S

Superior life and 10 year guarantee





10 year OSRAM guarantee

For a worry-free driving pleasure. Refer to www.osram.com/am-guarantee for precise conditions



Extra lifetime

Up to four times longer lifetime compared to standard xenon lamps



More durability

For longer replacement cycles and additional reliability and comfort



The durable light with up to four times longer lifetime

XENARC ULTRA LIFE xenon lamps were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers (www.osram.com/am-guarantee). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

Product datasheet

Technical data

Electrical Data

Power input	35 W
Nominal voltage	85.0 V
Nominal wattage	35 W
Power input tolerance	±3 %
Test voltage	13.5 V

Photometric Data

Nominal luminous flux	3200 lm
Luminous flux tolerance	±15 %
Color temperature	4300 K

Physical Attributes & Dimensions

Lamp base	P32d-2
Length	77.3 mm
Diameter	9 mm
Product weight	16.10 g

Lifetime Data

Capabilities

Technology	HID
------------	-----

Certificates & standards

ECE category	D2S ¹⁾
Approval marks – approval	E1 approval

 $^{^{1)}}$ To be operated only with approved electronic control gear

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of declaration	09-07-2024	
Primary article identifier	4062172404242 4052899425576 4052899429659	
Candidate list substance 1	Lead	
CAS No. of substance 1	7439-92-1	
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.	

Product datasheet

Declaration no. in SCIP database	ac5968cd-c357-48e1-9a75-7023de759a2e 0e906b5d-
	b5f0-4059-88bb-8de1f85d5ed2



 $ref_pim_amsp_productinfographic$

S

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899425583	XENARC ULTRA LIFE D2S		- x - x -	1.20 dm ³	
4062172022064	XENARC ULTRA LIFE D2S		- x - x -	1.56 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
人	Brochures ULTRA LIFE Leaflet EN
	ref_pim_amsp_product360degreeimages XENARC ULTRA LIFE D2S 66240ULT

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Application advice

For more detailed application information and graphics please see product datasheet.

Product datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

















