

# LEDDriving SL P21W



# Product datasheet

## Technical data

### Product information

Product type (off-road vs. on-road)	Off-road $\hat{=}$ P21W
Application (Category and Product specific)	Mainly used for signal/ indicator applications

### General Product Information

Global order reference	7506DWP
------------------------	---------

### Electrical Data

Power input	1.8 W
Nominal voltage	12.0 V
Nominal wattage	1 W
Test voltage	13.5 V
Power input tolerance	$\pm$ 25 %

### Photometric Data

Nominal luminous flux	160 lm
Luminous flux tolerance	$\pm$ 25 %
Color temperature	6000 K
Light color LED	Cool white

### Physical Attributes & Dimensions

Diameter	25.0 mm
Product weight	16.00 g
Length	52.5 mm
Lamp base	BA15s

### Lifetime Data

Lifespan B3	1500 hr
Lifespan Tc	4000 hr
Guarantee	4 years

### Capabilities

Technology	LED <sup>1)</sup>
------------	-------------------

<sup>1)</sup> Light-emitting diode lamp

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

## Product datasheet


Primary article identifier	4062172348652   4062172152181   4062172401210   4062172408318
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	e75f732e-151e-4392-9807-f15711d460b4

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172152181	LEDiving SL $\triangleq$ P21W	DK 2	135 mm x 95 mm x 18 mm	0.35 dm <sup>3</sup>	44.00 g
4062172152198	LEDiving SL $\triangleq$ P21W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm <sup>3</sup>	256.00 g
4062172401210	LEDiving SL $\triangleq$ P21W	BLI ECO 2	95 mm x 27 mm x 135 mm	0.35 dm <sup>3</sup>	43.00 g
4062172401227	LEDiving SL $\triangleq$ P21W	Shipping carton box 10	142 mm x 104 mm x 104 mm	1.54 dm <sup>3</sup>	250.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 Brochures LEDiving Retrofits - Exchange overview (EN)

#### Safety advice

Canbus compatible Coloured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

