

ALLSEASON SUPER / ALLSEASON H4

Extra visibility under all weather conditions



Extra visibility

Due to yellow coating



Up to 30% more light

For better visibility and significantly shorter reaction times compared to standard halogen lamps



Better sight

Under all weather conditions



Better sight under all weather conditions

With up to 30% more light compared to standard lamps and an interference yellow coating ALLSEASON and ALLSEASON SUPER improve visibility while on the road under all weather conditions.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	Halogen headlight lamp
---	------------------------

General Product Information

Global order reference	64193ALS
------------------------	----------

Electrical Data

Power input	75 / 68 W ¹⁾
Nominal voltage	12.0 V
Test voltage	13.2 V

¹⁾ Maximum

Photometric Data

Nominal luminous flux	1650/1000 lm
Luminous flux tolerance	±15 / ±15 %

Physical Attributes & Dimensions

Diameter	17.0 mm
Product weight	25.60 g
Length	82.0 mm
Lamp base	P43t

Lifetime Data

Lifespan B3	150 / 150 hr ¹⁾
Lifespan Tc	350 / 350 hr ¹⁾

¹⁾ Filament 1 / Filament 2

Capabilities

Technology	HAL
------------	-----

Certificates & standards

ECE category	H4
--------------	----

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	09-07-2024
Primary article identifier	4050300435978 4052899503311 4008321168559

Product datasheet

Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300435992	ALLSEASON SUPER / ALLSEASON H4		- x - x -	19.40 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM