


TECHNICAL FEATURES



Luminaire total power : 21.8W

Real lumens : 2106

Nominal lumens : 2106

Structure material : Steel, Aluminium, Acrylic

Structure finish : White

Diffuser material : Glass

Diffuser finish : Opal

Voltage / frequency : 100-240V/50-60Hz

Dimming protocol : ON-OFF

Power Factor : 0.90

Useful life : 36.000h L70B30

Warranty : 2 Years

LUMINOTECHNIC FEATURES

CRI: 80

MacAdam steps: 3

Photobiological risk: RG0

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	18.8W	LED warm-white 3000K

VENTILATION FEATURES

Blade finish: Transparent

Blade material: Acrylic

Maximum sound level (dB): 44

Minimum sound level (dB): 37

Maximum flow: 113.27

Power used: 21.8W

Service value: 5.20

Standby mode consumption: 0.5

Acoustic potential level: 44

Maximum air speed (m/s): 14870.21

Service value measurement standard: EN 60879:2019

	1	2	3	4	5
	95	120	144	165	200
W	8.5	13.4	21.1	31.8	50.2

EMERGENCY MODULE FEATURES


Battery type: PILA

LOGISTICS

Net weight (kg): 10.25

Packaged weight (kg): 11.68

Packaging: 695mm x 290mm x 355mm



LIGHT APPLICATION

